GÜTTLER®
SeedProfi Control

- Terminal with 5”- colour display
- Magnetic fixture
- Connecting cable 5 meters
- Electronic controlled seeding shaft drive with daily and total area acquisition
- Manual predosing
- Theoretical tank level indication
- Empty signal sensor
- More or less quantity in 5% - steps
- USB connection for updates
- Socket for lifting and speed signal
- Calibration and tank emptying button on the control box
- Two engine versions available:
  Basic: for pasture or small seeds
  High: for all seeds
  with fan speed and chain tear monitoring and stronger seed shaft motor

Precise seeding with GÜTTLER®

GÜTTLER®
Leading in soil structure

GÜTTLER® Electronic control
SeedProfi

NEW!



- More control
- Higher comfort

Consultation from:

GÜTTLER GmbH
Karl-Arnold-Straße 10 • D-73230 Kirchheim/Teck
☎ +49 70 21 98 57 0 • +49 159 01211824
info@guettler.de • www.guettler.de

GÜTTLER®
Leading in Soil Structure

1001 2614_EN_2023.10_Q_Except errors, subject to technical changes!

SeedProfi

It is now even easier to seed precisely and comfortably! The SeedProfi electronic control unit provides the customer with extensive monitoring of the system, the ability to change the seed rate while driving, and automatic calibration of the desired seed rate.

Higher control comfort

The SeedProfi was developed for the combination of GreenMaster with seeder for pastureland maintenance. But it is also ideal for sowing catch crops with the SuperMaxx® CULTI.

The **5-inch monitor** is very clear, and easy to operate. The menu is well-organised, and all settings can be found quickly.

The configuration can be chosen individually. There are **three different types of fan**: electric, hydraulic and mechanical.

The **speed** is transmitted to the seeder via the signal socket (optionally with impulse wheel) . The **tank level indication** of the seeder with calculated area performance or seeds completes the scope.


Seed calibration

By entering the desired sowing quantity, the SeedProfi electronic control unit automatically calibrates itself. Based on the calibration test, a minimum and maximum driving speed is displayed, as well as the actual speed.

From now on, use the facilitated calibration of the desired seed rate to control it while driving. Sowing has never been easier!

The situable dosing roller

We offer the situable dosing roller for all types of seed at different driving speeds:

8R1L		Dosing roller extra fine for very small quantities and small working width
8R1R		Dosing roller fine for fine seeds in large quantities e.g. for rape, mustard, clover
8R1S		Dosing roller medium for fine seeds in large quantities or with high speeds
8R3S		Dosing roller coarse - **standard equipment** for grass and catch crop mixture
8R2B		Dosing roller „extra coarse“ for very large quantities, hydraulic or mechanical fan recommended
8R1SD		Dosing roller „medium“ for fine seeds in small quantities below 5 kg/ha **NEW only for SeedProfi Basic/High**

- **Easy handling**
- **Monitoring of the most important parameters**
- **Independent calibration with calculation of the possible driving speed**
- **Easy seed quantity adjustment**
- **Seed data recording**
- **Seed predosing**
- **Daily and total area acquisition**



Control box with calibration and seed tank emptying button